



Amphenol's **H-Connector** assemblies provide a robust and sealed connection for outdoor fiber to the home (FTTH) connectivity.

The H-Connector incorporates an SC/APC type connection within a slim, sealed, threaded polymer housing allowing an easy and reliable outdoor connection.

Available with flat drop or round drop OSP cables, the H-Connector provides an ideal solution for direct burial, conduit or aerial installations.



Key Highlights



IP68 Ingress Protection



UV Stable Materials



Reliable factory grade **terminations**



Quick Connections Without Tools



Features and Benefits

- Factory terminated assemblies ensure high quality polish for reliable performance
- UV stable materials provide a long service life in direct sunlight areas
- Fully water sealed connections guarantee performance in harsh outdoor environments
- Low profile in-line receptacle assemblies allow pluggable extensions to splice closures
- Threaded couplings require no tools for fast and secure connections



Specifications

Ingress Protection (Mated)	IP68 (3 Meters/ 7 Days)
Mating Durability	500 cycles
Pull Force Retention	100lbs (445N)
Material	UV stable per GR-3120
Salt Mist	IEC 61300-2-26
Vibration	IEC 61300-2-1
Shock	IEC 61300-2-9
Operatina Temperature	-40°C to +75°C



Singlemode Insertion Loss ≤0.5dB Max (≤0.23dB Typical) per end

Singlemode ≥ 65dB **Return Loss**





H-Connector Plug Pigtail H-Connector Plug to Round SC Direct Connect Jumper H-Connector Plug to SC 2mm Breakout Jumper H-Connector In-Line Receptacle Pigtail H-Connector In-Line Receptacle to Round SC Direct Connect Jumper H-Connector In-Line Receptacle to SC 2mm Breakout Jumper